


elegant:  
A Flexible SDDS-Compliant Code  
for  
Accelerator Simulation

Michael Borland  
Operations Analysis Group  
Advanced Photon Source  
Argonne National Laboratory

## **SDDS** ***Self Describing Data Sets***

- An APS-developed file protocol and toolkit.
- Used with **elegant** and other simulations.
- Used by five accelerator laboratories for data archiving and control.
- ~70 general-purpose data analysis and display programs.
- Commandline-driven for easy use in scripts and automation.

## SDDS Toolkit Paradigm



## **General Capabilities of elegant *ELEctron Generation ANd Tracking***

- Tracking single and multipass machines.
- Perturbation/variation of accelerator parameters.
- Orbit/trajectory computation and correction.
- Optics calculations and correction.
- Optimization of tracked and computed quantities.
- Dynamic aperture determination.
- Generation of macro-particles with various distributions.
- Macro-particle data to/from SDDS files.
- Copious SDDS output of results.

## Sampling of SDDS Output Files from elegant

- turn-by-turn particle coordinates
- turn-by-turn beam moments
- turn-by-turn histograms
- coordinates of lost particles
- beam moments vs.  $s$
- transport matrix (up to 2nd order) vs.  $s$
- Twiss parameters and radiation integrals vs.  $s$
- lattice parameters (chromaticities, emittance, etc.)
- internally-generated error values

## Overview of Physics in elegant

- Track in 6D with matrices, canonical integration, numerical integration, or mixture.
- Time-dependent elements: rf cavity, rf deflector, kicker, traveling wave linac, etc.
- Collective effects: impedances, CSR, IBS\*.
- SASE FEL computations.
- Collimators and scrapers.
- Quantum excitation\*, radiation damping\*, scattering.
- Misalignments.


\*rings only.

## **Some Accelerator Projects Accomplished Using elegant**

- Tracking simulations for SSRL preinjector\*
- Design of beamline for APS thermionic rf gun
- Design of APS Positron Accumulator Ring\*
- Top-up safety tracking for APS storage ring
- Low-emittance lattices for APS storage ring
- Dual insertion device lattices for APS storage ring
- Design of APS bunch compressor and redesign of linac
- Sensitivity analysis and jitter simulation for LCLS

\*Used MAD for matching.

## Example: Direct Injection from APS Linac to Booster







## Simulation Details

- generate 24 bunches at 2856 MHz
- provide linear energy ramp (SDDS file)
- provide  $\sim E^4$  rf ramp (SDDS file)
- include radiation damping and quantum excitation
- gated vertical tune driver as bucket cleaner (SDDS file)
- run for 40 combinations of injection energy and initial rf voltage

## Organization of Simulations




## Summary of Direct Injection Efficiency



## **Example: APS Bunch Compressor Design**

- Started in Summer 1999 as part of push to saturate LEUTL FEL.
- Secondary goal was to explore CSR.
- Design incorporates movable magnets to allow variable  $R_{56}$  and asymmetry.
- Short design and construction schedule benefitted from automation of simulation tasks.
- System in operation since late July 2000.

## APS Linac/Compressor Schematic




## Simulation Tasks for APS Bunch Compressor

- Select a set of chicane configurations, i.e.,  $R_{56}$  and asymmetry.
- Select target currents (e.g., 300A) and acceleration profiles.
- For each configuration
  - Perform longitudinal matching via tracking.
  - Perform transverse matching.
  - Track with wakefields and CSR.
  - Determine jitter sensitivity.
  - Track with random errors to verify tolerances.

## **What Was Accomplished with Bunch Compressor Simulations**


- About 50 configurations were produced and examined in an automated fashion.
- Rapidly evaluated proposed (engineering) changes.
- Produced data for automated setup of accelerator.
- Found trends in emittance, gain length, etc. across a wide range of conditions.
- Found jitter sensitivity and identified least sensitive configurations.
- Produced tolerance requirements.
- Explored impact of relaxed tolerances.

## Performance Variation Prediction






## Phase Sensitivity Result



## Sample Data from Jitter Simulation



BORLAND/aps/bunchComp/VaryL3/optics6.0/300A-1 40.21 7MeV-65mm2/allJitter/SOA

## Summary

- **elegant** is a flexible code
  - well suited to complex projects
  - incorporating a wide variety of physics
  - incorporating unique features
  - applied to numerous real-world problems
- The SDDS toolkit
  - provides the sole pre- and post-processing software
  - enhances **elegant** dramatically